

L114

80G SEMIGLOSS PAPER/A02/60G WHITE GLASSINE

GENERAL DESCRIPTION

Our paper's stellar conversion performance ensures it's suitable for both rotary and flatbed applications. It prints beautifully on offset, UV letterpress, and UV flexo presses, making it a perfect choice for large-scale solid printing. However, during the printing process, please ensure to monitor ink viscosity, as excessively high viscosity can harm the paper's surface.



TECHNICAL DATA

CODE	L114	
MODEL	80g Semigloss Paper/A02/60g White Glassine	
FACESTOCK	80g Semigloss Paper	
ADHESIVE	A02(an acrylic water based permanent adhesive)	
LINER	60g White Glassine	
ITEM	SPECIFICATION	UNIT
FACESTOCK		
BASIC WEIGHT	80±8	g/m ²
CALIPER	60±6	µm
ADHESIVE		
LOOP TACK FTM 9	≥12 or Tear	N/in
20 MIN 90° PEEL FTM2	≥7 or Tear	N/in
24 HR 90° PEEL FTM2	≥8 or Tear	N/in
LINER		
BASIC WEIGHT	60±6	g/m ²
CALIPER	52±5	µm
STORAGE CONDITION	Temperature 23±2°C Humidity 65±5%	

WIDTH/LENGTH

Jumbo rolls: 1070mm/1530mm * 4000/6000m, Core ID 3"

Slitted rolls: 70/80/... mm * 300/.../2000/3000/4000/...m, Core ID 3"

WARRANTY

12 months from delivery date



Hangzhou Onward Material Co. Ltd.

Website: www.onwardhz.com

Email: onward@onwardhz.com

Tel: 0571-87680533

Fax: 0571-87680533