

L138

60µ BRIGHT WHITE PP/A103/60G WHITE GLASSINE

GENERAL DESCRIPTION

The stellar conversion performance ensures it can be utilized effectively in both rotary and flatbed applications. It offers exceptional printing quality on offset, UV letterpress, and UV flexo presses, making it an ideal choice for large-scale solid printing. However, it's crucial to maintain caution during the printing process regarding ink viscosity, as excessively high viscosity can potentially damage the film's surface.



TECHNICAL DATA

CODE	L138	
MODEL	60μ Bright White PP/A103/60g White Glassine	
FACESTOCK	60μ Bright White PP	
ADHESIVE	A103 (an acrylic water based permanent adhesive)	
LINER	60g White Glassine	
ITEM	SPECIFICATION	UNIT
FACESTOCK		
BASIC WEIGHT	43±4	g/m²
CALIPER	60±6	μm
ADHESIVE		
LOOP TACK FTM 9	≥8	N/in
20 MIN 90° PEEL FTM2	≥5	N/in
24 HR 90° PEEL FTM2	≥6	N/in
LINER		
BASIC WEIGHT	60±6	g/m²
CALIPER	52±5	μm
STORAGE CONDITION	Temperature 23±2°C Hu	umidity 65±5%

WIDTH/LENGTH

Jumbo rolls: 1070mm/1530mm * 4000/6000m, Core ID 3"

Slitted rolls: 70/80/... mm * 300/.../2000/3000/4000/...m, Core ID 3"

WARRANTY

12 months from delivery date



Hangzhou Onward Material Co. Ltd. Website: www.onwardhz.com Email: onward@onwardhz.com

Tel: 0571-87680533 Fax: 0571-87680533