

L139

50μ TRANSPARENT PP/A103R/60G WHITE GLASSINE

GENERAL DESCRIPTION

The robust conversion performance enables its use in rotary and flatbed applications. It prints brilliantly on offset, UV letterpress, and UV flexo, ideal for large solid prints. But be mindful of ink viscosity during printing; high viscosity can damage the film's surface.



TECHNICAL DATA

CODE	L139	
MODEL	50μ Transparent PP/A103R/60g White Glassine	
FACESTOCK	50μ Transparent PP	
ADHESIVE	A103R (an acrylic water based permanent adhesive)	
LINER	60g White Glassine	
ITEM	SPECIFICATION	UNIT
FACESTOCK		
BASIC WEIGHT	44±4	g/m ²
CALIPER	50±5	μm
ADHESIVE		
LOOP TACK FTM 9	≥7	N/in
20 MIN 90° PEEL FTM2	≥5	N/in
24 HR 90° PEEL FTM2	≥6	N/in
LINER		
BASIC WEIGHT	60±6	g/m ²
CALIPER	52±5	μm
STORAGE CONDITION	Temperature 23±2°C	Humidity 65±5%

WIDTH/LENGTH

Jumbo rolls: 1070mm/1530mm * 4000/6000m, Core ID 3"

Slitted rolls: 70/80/... mm * 300/.../2000/3000/4000/...m, Core ID 3"

WARRANTY

12 months from delivery date



Hangzhou Onward Material Co. Ltd.

Website: www.onwardhz.com

Email: onward@onwardhz.com

Tel: 0571-87680533

Fax: 0571-87680533