

L112

80G SEMIGLOSS PAPER/B14/60G WHITE GLASSINE

GENERAL DESCRIPTION

Our paper offers exceptional conversion performance, suitable for both rotary and flatbed applications. It boasts superior printing quality on offset, UV letterpress, and UV flexo presses, making it ideal for large-scale solid printing. However, it's crucial to monitor ink viscosity during the printing process, as excessively high viscosity can damage the paper's surface.



TECHNICAL DATA

CODE	L112	
MODEL	80g Semigloss Paper/B14/60g White Glassine	
FACESTOCK	80g Semigloss Paper	
ADHESIVE	B14 (a rubber based permanent adhesive)	
LINER	60g White Glassine	
ITEM	SPECIFICATION	UNIT
FACESTOCK		
BASIC WEIGHT	80±8	g/m ²
CALIPER	60±6	µm
ADHESIVE		
LOOP TACK FTM 9	≥11 or Tear	N/in
20 MIN 90° PEEL FTM2	≥7 or Tear	N/in
24 HR 90° PEEL FTM2	≥8 or Tear	N/in
LINER		
BASIC WEIGHT	60±6	g/m ²
CALIPER	52±5	µm
STORAGE CONDITION	Temperature 23±2°C	Humidity 65±5%

WIDTH/LENGTH

Jumbo rolls: 1070mm/1530mm * 4000/6000m, Core ID 3"

Slitted rolls: 70/80/... mm * 300/.../2000/3000/4000/...m, Core ID 3"

WARRANTY

12 months from delivery date



Hangzhou Onward Material Co. Ltd.

Website: www.onwardhz.com

Email: onward@onwardhz.com

Tel: 0571-87680533

Fax: 0571-87680533