

L137

50 μ TRANSPARENT PP/A104R/30 μ PET

GENERAL DESCRIPTION

The product excels in rotary and flatbed conversion while requiring careful tension control to prevent bleeding. It also prints well on offset, UV letterpress, and UV flexo, suitable for large solid prints. Maintaining proper ink viscosity during printing is key to protect the paper's surface.



TECHNICAL DATA

CODE	L137	
MODEL	50 μ Transparent PP/A104R/30 μ PET	
FACESTOCK	50 μ Transparent PP	
ADHESIVE	A104R (an acrylic water based permanent adhesive)	
LINER	30 μ PET	
ITEM	SPECIFICATION	UNIT
FACESTOCK		
BASIC WEIGHT	44 \pm 4	g/m ²
CALIPER	50 \pm 5	μ m
ADHESIVE		
LOOP TACK FTM 9	\geq 7	N/in
20 MIN 90° PEEL FTM2	\geq 5	N/in
24 HR 90° PEEL FTM2	\geq 6	N/in
LINER		
BASIC WEIGHT	42 \pm 4	g/m ²
CALIPER	30 \pm 3	μ m
STORAGE CONDITION	Temperature 23 \pm 2°C Humidity 65 \pm 5%	

WIDTH/LENGTH

Jumbo rolls: 1070mm/1530mm * 4000/6000m, Core ID 3"

Slitted rolls: 70/80/... mm * 300/.../2000/3000/4000/...m, Core ID 3"

WARRANTY

12 months from delivery date



Hangzhou Onward Material Co. Ltd.

Website: www.onwardhz.com

Email: onward@onwardhz.com

Tel: 0571-87680533

Fax: 0571-87680533