

L115

80G SEMIGLOSS PAPER/B13/60G WHITE GLASSINE

GENERAL DESCRIPTION

The product boasts versatile paper conversion performance for rotary and flatbed use, but excessive re-winding tension should be avoided to prevent bleeding. It also performs well in offset, UV letterpress, and UV flexo printing, suitable for large solid prints. However, managing ink viscosity during printing is key to prevent surface damage.



TECHNICAL DATA

CODE	L115	
MODEL	80g Semigloss Paper/B13/60g White Glassine	
FACESTOCK	80g Semigloss Paper	
ADHESIVE	B13 (a rubber based permanent adhesive)	
LINER	60g White Glassine	
ITEM	SPECIFICATION	UNIT
FACESTOCK		
BASIC WEIGHT	80±8	g/m ²
CALIPER	60±6	µm
ADHESIVE		
LOOP TACK FTM 9	≥17 or Tear	N/in
20 MIN 90° PEEL FTM2	≥10 or Tear	N/in
24 HR 90° PEEL FTM2	≥11 or Tear	N/in
LINER		
BASIC WEIGHT	60±6	g/m ²
CALIPER	52±5	µm
STORAGE CONDITION	Temperature 23±2°C	Humidity 65±5%

WIDTH/LENGTH

Jumbo rolls: 1070mm/1530mm * 4000/6000m, Core ID 3"

Slitted rolls: 70/80/... mm * 300/.../2000/3000/4000/...m, Core ID 3"

WARRANTY

12 months from delivery date



Hangzhou Onward Material Co. Ltd.

Website: www.onwardhz.com

Email: onward@onwardhz.com

Tel: 0571-87680533

Fax: 0571-87680533