

# L116

## 80G SEMIGLOSS PAPER/B15/60G WHITE GLASSINE

### GENERAL DESCRIPTION

Our premium paper boasts exceptional conversion capabilities, ideal for both rotary and flatbed processes. Maintaining proper ink viscosity during printing is crucial to preserve the paper's surface integrity. Full-solid printing and fine barcode printing are advised against. Additionally, prevent bleeding by avoiding excessive tension during rewinding.



### TECHNICAL DATA

| CODE                 | L116                                       |                  |
|----------------------|--|------------------|
| MODEL                | 80g Semigloss Paper/B15/60g White Glassine |                  |
| FACESTOCK            | 80g Semigloss Paper                        |                  |
| ADHESIVE             | B15 (a rubber based permanent adhesive)    |                  |
| LINER                | 60g White Glassine                         |                  |
| ITEM                 | SPECIFICATION                              | UNIT             |
| <b>FACESTOCK</b>     |  |                  |
| BASIC WEIGHT         | 80±8                                       | g/m <sup>2</sup> |
| CALIPER              | 69±6                                       | µm               |
| <b>ADHESIVE</b>      |  |                  |
| LOOP TACK FTM 9      | ≥13 or Tear                                | N/in             |
| 20 MIN 90° PEEL FTM2 | ≥9 or Tear                                 | N/in             |
| 24 HR 90° PEEL FTM2  | ≥10 or Tear                                | N/in             |
| <b>LINER</b>         |  |                  |
| BASIC WEIGHT         | 58±5                                       | g/m <sup>2</sup> |
| CALIPER              | 50±5                                       | µm               |
| STORAGE CONDITION    | Temperature 23±2°C                         | Humidity 65±5%   |

### WIDTH/LENGTH

Jumbo rolls: 1070mm/1530mm \* 4000/6000m, Core ID 3"

Slitted rolls: 70/80/... mm \* 300/.../2000/3000/4000/...m, Core ID 3"

### WARRANTY

12 months from delivery date



Hangzhou Onward Material Co. Ltd.

Website: [www.onwardhz.com](http://www.onwardhz.com)

Email: [onward@onwardhz.com](mailto:onward@onwardhz.com)

Tel: 0571-87680533

Fax: 0571-87680533