

L191

70G DIRECT THERMAL PAPER/B40/60G WHITE GLASSINE

GENERAL DESCRIPTION

The product's fair paper conversion performance makes it suitable for use in simple rotary and flatbed printing applications. To prevent bleeding, it's important to avoid excessive re-winding tension. However, due to its thermal activity limitations, the product cannot be printed under high temperature conditions (<50°C), and the DT topcoat should not be exposed to alcohol.



TECHNICAL DATA

CODE	L191	
MODEL	70g Direct Thermal Paper/B40/60g White Glassine	
FACESTOCK	70g Direct Thermal Paper	
ADHESIVE	B40 (a rubber based permanent adhesive)	
LINER	60g White Glassine	
ITEM	SPECIFICATION	UNIT
FACESTOCK		
BASIC WEIGHT	70±7	g/m ²
CALIPER	65±6	µm
ADHESIVE		
LOOP TACK FTM 9	≥10 or Tear	N/in
20 MIN 90° PEEL FTM2	≥7 or Tear	N/in
24 HR 90° PEEL FTM2	≥8 or Tear	N/in
LINER		
BASIC WEIGHT	60±6	g/m ²
CALIPER	52±5	µm
STORAGE CONDITION	Temperature 23±2°C	Humidity 65±5%

WIDTH/LENGTH

Jumbo rolls: 1070mm/1530mm * 4000/6000m, Core ID 3"

Slitted rolls: 70/80/... mm * 300/.../2000/3000/4000/...m, Core ID 3"

WARRANTY

12 months from delivery date



Hangzhou Onward Material Co. Ltd.

Website: www.onwardhz.com

Email: onward@onwardhz.com

Tel: 0571-87680533

Fax: 0571-87680533